

TECHNICAL SPECIFICATIONS

Dimensions	
$(H \times W \times D)$	62.2 x 34.2 x 30.4 cm
Flowrate	0.5 to 5 l/min
Oxygen	at 0.5 - 5 I/min
Concentration	93% ± 3%
Electrical	230V
Ratings	50 Hz, 3.2A
Weight	16.3 kilograms
Power	approx. 290 Watt at 2 I/
Consumption	min
	approx. 312 Watt at 5 I/min

Classification II Type B

Drive DeVilbiss Compact 525 5 Litre Oxygen Concentrator

Manufacturing products that are of the highest possible quality is key to Drive DeVilbiss International. The Compact 525 oxygen concentrator is designed and built to meet the ever growing demands of patient care and the economical challenges faced by service providers

Delivering up to 5 litres per minute with high oxygen concentration across all flow rates and adopting the latest developments in the reduction of sound and power consumption, the Compact 525 increases patient comfort and lowers operating costs.

Added features

- Improved sound level reduction our quietest concentrator yet
- Front label with easy to read pictograms
- Integrated handle and castors for easy transport
- Simple to start-up and easy to use

Service and maintenance friendly

- 2 part case design
- 3 years warranty as standard (an optional extended 2 year warranty package available)

Patient safety features

- OSD® Sensor for continuously monitoring oxygen levels
- Visual and audible alarms for low oxygen levels, power failure, low pressure and service required
- Oxygen outlet incorporating a fire protection technology

Environmentally friendly

- Intelligent power management system utilises Turn-Down Technology providing less power consumption at lower flow rates
- Reduced packaging: reducing materials and waste, as well as transportation costs and emissions - without compromising product protection



Front label with easy to read pictograms



Humidifier (optional)



Paediatric Flowmeter (optional)



